APPLICATION OVERVIEW GROUPED BRACKET FIXED LOUVRES AT GLANCE

MINIMUM - MAXIMUM BLADE SPANS AT A GLANCE AS DETERMINED BY WIND SPEED. REFER TO SECTION ENGINEERING REPORTS FOR FULL DETAILS ON BLADE SPANS.

EXTRA HIGH WIND SPEED 198KM/H 55M/S

LOW WIND SPEED 115KM/H 32M/S

THE LOUVRETEC RANGE OF BRACKET FIXED SUN LOUVRES
7 Groups of Sun Louvres that can be Bracket Fixed using Louvretec's proprietary Bracket Fixing system
IF A LOUVRE YOU WISH TO SPECIFY IS NOT SHOWN IN THIS SECTION PLEASE CONTACT YOUR DEALER. WE'RE FOCUSED TO MEETING YOUR NEEDS WITH TAILORED SOLUTIONS.

GROUP	LOUVRE	MAXIMUM SPANS
BRACKET FIXED GROUP 1	90 MIDI LOUVRE	1400MM (EX HIGH) / 2000MM (LOW)
	150 MIDI LOUVRE	1900MM (EX HIGH) / 2750MM (LOW)
BRACKET FIXED GROUP 2	120 AIRFOIL LOUVRE	1600MM (EX HIGH) / 2300MM (LOW)
	180 AIRFOIL LOUVRE	2050MM (EX HIGH) / 2950MM (LOW)
BRACKET FIXED GROUP 3	200 MAXI LOUVRE	2350MM (EX HIGH) / 3700MM (LOW)
BRACKET FIXED GROUP 4	300 MAXI LOUVRE	3350MM (EX HIGH) / 4800MM (LOW)

APPLICATION OVERVIEW GROUPED BRACKET FIXED LOUVRES AT A GLANCE

MINIMUM – MAXIMUM BLADE SPANS AT A GLANCE AS DETERMINED BY WIND SPEED. REFER TO SECTION ENGINEERING REPORTS FOR FULL DETAILS ON BLADE SPANS.

EXTRA HIGH WIND SPEED 198KM/H 55M/S

LOW WIND SPEED 115KM/H 32M/S

THE LOUVRETEC RANGE OF BRACKET FIXED SUN LOUVRES
7 Groups of Sun Louvres that can be Bracket Fixed using Louvretec's proprietary Bracket Fixing system
IF A LOUVRE YOU WISH TO SPECIFY IS NOT SHOWN IN THIS SECTION PLEASE CONTACT YOUR DEALER. WE'RE FOCUSED TO MEETING YOUR NEEDS WITH TAILORED SOLUTIONS.

GROUP	LOUVRE	MAXIMUM SPANS
BRACKET FIXED GROUP 5	150MM HELENA BAY	2050MM (EX HIGH) / 3050MM (LOW)
	125MM WEATHERBOARD PANEL	1750MM (EX HIGH) / 2500MM (LOW)
	180MM WEATHERBOARD PANEL	2100MM (EX HIGH) / 3050MM (LOW)
END FIXED GROUP 6	600 MAXI LOUVRE	3700MM (EX HIGH) / 5800MM (LOW)
END FIXED GROUP 7	RL300 MITRE LOUVRE	4050MM (EX HIGH) / 5800MM (LOW)
	RL450 MITRE LOUVRE	4050MM (EX HIGH) / 5800MM (LOW)
	RL600 MITRE LOUVRE	4050MM (EX HIGH) / 5800MM (LOW)
	RL300 SQUARE LOUVRE	4050MM (EX HIGH) / 5800MM (LOW)
	RL450 SQUARE LOUVRE	4050MM (EX HIGH) / 5800MM (LOW)
	RL600 SQUARE LOUVRE	4050MM (EX HIGH) / 5800MM (LOW)